Personal Fall Limiter
by Buckingham

The BuckLimiter
BENEFITS & FEATURES

- Just 1.9 lbs! Compact design and use of advanced materials provide a light weight retractable unit.
- Aluminum Alloy Construction Inside & Out: both the mechanism and housing made of corrosion resistant alloy.
- Tangle free swivel top for added mobility.
- 7' extension for expanded work area.
- Dyneema® polymer fiber 1" webbing - up to 15x stronger than steel. Resistant to moisture, abrasions, UV light and chemicals.
- A braking system designed for smooth consistent operation to prevent "jerky" lock-ups.
- No factory recertification required.
- Available in models that meets ASTM F887 Electric Arc Performance Requirements. Use prefix 6008K; e.g. 6008K-74+X+4+Z.

BuckLimiter
Model 6008-74+X+4+Z

1.9 lbs. of Tough Performance Configured to Your Specifications!

(See Hardware Matrix on Back)

BuckLimiter
Model 6008-74+X+4+Z
Shown on a Buckfit Harness

Buckingham Manufacturing Co., Inc.
Tel. 1-800-YES-BUCK (1-800-937-2825)
www.buckinghammfg.com

ISO 9001:2000 Certified

Personal Fall Limiter
by Buckingham

BuckLimiter
HARDWARE MATRIX

Retractable Unit	Length In Feet	Swivel	Connecting Device (swivel end)*	Connecting Device (web end)*
6008 - Single PFL 6008K - Single PFL Meets ASTM F887 Electric Arc Performance Rqmts.	7'	4 = Swivel Built in	D = P/N 50051 Steel Carabiner w/ 3600 lb. Gate +X = Aluminum Carabiner meets Z359.1 (3600 lbs gate)	+4 = 2 1/4" locking ladder snap 3035 or when used w/ option +Z, a 30351 w/ 3600lb gateload D = P/N 50051 Steel Carabiner w/ 3600 lb. Gate V = 1706 Snap or when used w/ option +Z, a 17061 w/ 3600lb gateload +X = Aluminum Carabiner meets Z359.1 (3600 lbs gate) +Z = All hardware on lanyard meets Z359-07 3600 lb gate load *Load Capacity = 310 lbs.

BuckLimiter
Model 6008-74DV+Z

BuckLimiter
Built In Swivel for Easier Movement

Buckingham Manufacturing Co., Inc.
Tel. 1-800-YES-BUCK (1-800-937-2825)
www.buckinghammfg.com

ISO 9001:2000 Certified