ARBORMASTER® FRICTION SAVERS

[PATENTED]

BENEFITS INCLUDE:

- Installation and retrieval from the ground
- Less bend radius
- Less friction - easier to climb
- Reduced wear to rope
- Can be used as false crotch
- Rated for human support only
- Available in steel and hard coat anodized aluminum

Model 57-24

Anodized Aluminum	Steel	
Model Number	Model Number	Overall Length
57-24	57S-24	2'
57-36	57S-36	3'
57-48	57S-48	4'
57-60	57S-60	5'
57-72	57S-72	6'

INSTALLATION METHODS

FRICTION SAVERS:

- Using throw line, place throw bag over a solid branch
- With throw bag on the ground, tie throw bag on the outside of the small ring on the friction saver
- Insert the other end of throw line into the large ring
- Using the throw line inserted through the large ring, proceed to pull until the throw bag just reaches the branch
- Giving a quick tug, pull the throw bag over branch and let it drop to the ground
- With the friction saver now over the branch, tie the climbing line onto one end of the throw line and pull through the rings

ADJUSTABLE FRICTION SAVER

- **Friction Saver Prusik Loop with Aluminum Rings**
- Offers numerous benefits while climbing, working, and descending a tree without limbs or limbs inaccessible by a throw bag and line.

Model 704A1

To order with steel rings:
Model 704S1